

COG Software Architecture Design Description Document

Richard M. Buck Edward M. Lent

September 15, 2009

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Auspices Statement

This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

COG

Software Architecture Design Description Document

Prepared by: <u>Signature on File</u>

Richard M. Buck

COG Code Developer

Prepared by: <u>Signature on File</u>

Edward M. Lent

COG Code Developer

Reviewed by: <u>Signature on File</u>

Darrel M. Whitney

Software Quality Assurance Manager

Approved by: <u>Signature on File</u>

David P. Heinrichs

Nuclear Criticality Safety Division Leader

Document Revision History

Revision	Date	Description
0	9-12-09	ISQAP requirement per CSAM 08-086, SQA Gap Analysis for COG

Table of Contents

1.	Introducti	ion	1
	1.1. Purp	ose	1
	1.2. Scope	e	1
	1.3. Orga	nization	1
2.	Reference	2S	2
3.	Software 1	Design	3
	3.1. Requ	iirements	3
		ctives	
	3.3. Code	Modules	3
	3.3.1.	Principal Code Modules	3
	3.3.2.	Other Code Modules (Alphabetical Listing)	5
		ational Phases	
	3.5. Flow	Diagrams by Operational Phase	6
	3.5.1.	Input Phase Modules	7
	1.	Geom Module Input Phase Routines	7
	2.	Sor Module Input Phase Routines	8
	3.	Det Module Input Phase Routines	
	4.	RW Module Input Phase Routines	11
	5.	TXS Module Input Phase Routines	12
	6.	EGS Module Input Phase Routines	14
	7.	Pro Module Input Phase Routines	15
	3.5.2.	Transport Phase Modules	16
	1.	RW Module Transport Phase Routines	17
	2.	Geom Module Transport Phase Routines	20
	3.	Det Module Transport Phase Routines	20
	4.	Sor Module Transport Phase Routines	22
	5.	TXS Module Transport Phase Routines	23
	3.5.3.	Output Phase Modules	25
	1.	Geom Module Output Phase Routines	25
	2.	Det Module Output Phase Routines	
	3.	RW Module Output Phase Routines	28
	4.	TXS Module Output Phase Routines	29
	3.5.4.	Utility Routines	29
	1.	Mem module routines	29
	2.	TXS module routines	30
	3.	RW module routines	
	3.5.5.	Externally-Provided Software	30
		Structures	
	3.6.1.	Geometry Data Structures	30
	1.	Surface Data Storage	30
	2.	Volume Data Storage	39
	3.6.2.	Event History Storage (EHS) Data Structures	
		Input File	

3.6.4. Common Block Usage	42
INDEX	43
List of Tables	
Table 1 Internal Surface Types	31
Table 2 Surface Definition Data Storage	
Table 3 Sector Description (sd) Array	40
Table 4 Event History Store Record	41
Table 5 Events	42

1. INTRODUCTION

1.1.Purpose

This COG Software Architecture Design Description Document describes the organization and functionality of the COG Multiparticle Monte Carlo Transport Code for radiation shielding and criticality calculations, at a level of detail suitable for guiding a new code developer in the maintenance and enhancement of COG. The intended audience also includes managers and scientists and engineers who wish to have a general knowledge of how the code works. This Document is not intended for end-users.

1.2.Scope

This document covers the software implemented in the standard COG Version 10, as released through RSICC and IAEA. Software resources provided by other institutions will not be covered.

1.3. Organization

This document presents the routines grouped by modules and in the order of the three processing phases. Some routines are used in multiple phases. The routine description is presented once – the first time the routine is referenced. Since this is presented at the level of detail for guiding a new code developer, only the routines invoked by another routine that are significant for the processing phase that is being detailed are presented. An index to all routines detailed is included.

Tables for the primary data structures are also presented.

2. REFERENCES

- CSAM 08-086, SQA Gap Analysis for COG, Nuclear Criticality Safety Division, Lawrence Livermore National Laboratory, September 3, 2008.
- IEEE Std 1016-1998, *IEEE Recommended Practice for Software Design Descriptions*, Institute of Electrical and Electronics Engineers, Inc., September 23, 1998.
- SBK08-085, Memorandum of Understanding between the Nuclear Materials Technology Program (NMTP) and Nuclear Operations (NucOps), Lawrence Livermore National Laboratory, April 30, 2008.
- UCRL-TM-202590, COG, A Multiparticle Monte Carlo Transport Code, User's Manual, Fifth Edition, Lawrence Livermore National Laboratory, September 1, 2002.
- http://cog.llnl.gov

3. SOFTWARE DESIGN

3.1.Requirements

The basic requirement is to develop a code package that will implement best-ofclass Monte Carlo particle transport methods to solve radiation shielding and nuclear criticality problems involving complex 3D geometry, multiparticle sources, arbitrary materials, and many detector types.

3.2. Objectives

Given that the requirements necessitate a large and complex software package, functional decomposition was used. As far as possible, major code operations were decomposed into code modules that perform single functions. For example, the handling of geometry, sources, materials, and detectors is performed in appropriately named modules, each of which is a code source directory.

3.3. Code Modules

A Code Module is conceptually a collection of Source routines that implement a major code function or feature, such as particle detector simulation. A Module is instantiated as a file system directory containing Source files, such as the Det directory. For every Source Module, there is a corresponding object library file, such as libDet.a. The COG code is generated by compiling all Source Modules into object libraries, then linking the library files.

3.3.1. Principal Code Modules

Main (Main Module)

Purpose	Functions
Controls the execution of the	Calls routines that read the input file, set up the
user's job.	computation, track the source particles through
	the problem's geometry, and output results.

Geom (Geometry Module)

Purpose	Functions
Reads and stores input file	Reads entire input file.
data that specify the	Checks for input syntax errors.
problem's geometry and	Processes and stores input-file Basic Block data.
material composition.	Processes and stores input-file Geometry Block
	data.
	Processes and stores input-file Mix Block data.
	Optionally, helps detect geometry setup errors by:
	making sweeps through the geometry;
	making 2D and perspective pictures of the user's
	geometry; calculating object volumes.

Sor (Source Module)

Purpose	Functions
Reads and stores input file	Processes and stores input-file Source Block data.
data that specify the	Produces pictures of source particle emission to
problem's particle sources.	aid in verifying source descriptions.
	During Transport phase, produces source
	particles for tracking through geometry.

Det (Detector Module)

D	T
Purpose	Functions
Reads and stores input file	Processes and stores input-file Detector Block
data that specify the	data.
problem's particle detectors.	Produces pictures of source particle emission to aid in verifying source descriptions.
	Reads/writes restart dumps.
	During Transport phase, scores particles that reach detectors.
	During Output phase, prints and plots detector results.

RW (Random Walk Module)

Purpose	Functions
Performs tracking of source	Processes and stores input-file Walk-XX Block
particles through the	data.
problem's geometry and	Processes and stores input-file Activation Block
materials.	data.
	During Transport phase, tracks one particle at a
	time through the problem's geometry, using
	optional Walk-XX Block parameters to improve
	performance.
	During Output phase, makes analysis plots.

TXS (Total Cross Section Module)

Purpose	Functions
Handles the physics data that	Reads physics databases and creates particle
determine collision	collision data for the materials in the problem.
probabilities and outcomes	During Transport phase, provides cross-section
for particle transport.	data and collision outcomes to the RW module.

EGS (Electron Gamma-Ray Shower Module)

Purpose	Functions
Transports electrons through	Processes and stores input-file EGS Block data.
the problem's geometry.	During Transport phase, tracks one electron at a
	time through the problem's geometry,

Pro (Proton Transport Module)

Purpose	Functions
Transports protons through	Processes and stores input-file Pro Block data.
the problem's geometry.	During Transport phase, tracks one proton at a
	time through the problem's geometry,

3.3.2. Other Code Modules (Alphabetical Listing)

Grf (Graphics Module)

Purpose	Functions
Supports COG graphics.	Enables plotting to screen or file in choice of
	colors, lines, points, mappings.
	Communicates with lower-level PGPLOT library
	routines.

include (Include Module)

Purpose	Functions
Contains all "include" files	Collects all include files in one directory.
needed by COG.	

LF (Lagged Fibonacci Random Number Generator Module)

Purpose	Functions
Provides psuedo-random	Processes and stores the starting random number
numbers for the Monte Carlo	seeds for the job.
aspects of COG.	During Transport phase, provides a series of
-	psuedo-random numbers to the Sor and RW
	modules.

Mag (Magnetic Field Module)

Purpose	Functions
Calculates charged particle	Processes and stores input-file Mag Block data.
motion in a vacuum	During Transport phase, steps particle through
magnetic field.	specified magnetic fields.

Mem (Memory Management Module)

Purpose	Functions
Improves memory	Wraps Unix memory management routines to
diagnostics	provide better diagnosis of memory allocation
	errors.

MPI (Message Passing Interface Module)


Purpose	Functions
Permits COG parallel	Processes and stores input-file Parallel Block
processing	Data.
	Sets up a parallel Master/Slave run under the MPI
	system.
	During Transport phase, passes messages
	between Master and Slave processes to enable
	the simultaneous execution of multiple copies of
	COG on one input file.

PP (Parallel Processing Support Module)

Purpose	Functions
Supports COG parallel	Sums up results over all Slave processes.
processing	

3.4. Operational Phases

An **Operational Phase** is a logical division of the workflow that COG performs during the running of a user's job. These divisions are chosen to represent distinct major tasks. The phase breakdown we have chosen is: Input, Transport, and Output.



Input Phase - Read and process input file and library files.
 Transport Phase - Calculate particle trajectories and scoring.
 Output Phase - Create output listing and make pictures of results.

3.5. Flow Diagrams by Operational Phase


The following steps through the operational phases and describes the routines within each primary module that are used for that phase. Routines from a different module are indicated with a prefix such as RW:.

3.5.1. Input Phase Modules

Routines from the following Modules are used in the Input Phase in the following order:

- Geom
- Sor
- Det
- RW
- TXS
- EGS
- Pro

1. Geom Module Input Phase Routines



ffinp

Reads the COG input file and parses it into symbols.

Parsed symbols are stored as character strings and as numbers.

Symbols are scanned to locate Data Block names and identify the beginning and end of each Block.

geomin

Processes these parsed Data Blocks:

ASSIGN SURFACES GEOMETRY

asmrd

Processes ASSIGN Data Blocks.

Assigns materials, densities, scoring region numbers to sectors.

surfac

Processes SURFACES Data Block.


Computes a mathematical model for each surface and stores coefficients.

unitrd

Processes GEOMETRY Data Block.

Generates and stores sector descriptions based on bounding surfaces.

2. Sor Module Input Phase Routines



<u>sorin</u>

Processes the parsed SOURCE Data Block. Creates the particle source from the Source description to be used during the Transport Phase.

critin

Processes the source specification for a criticality job.

----Routines that process the Source dependence on location, energy, angle, and time----

rsp

Processes the Source Position specification. Plots 1500 samples chosen from this specification.

rse

Processes the Source Energy specification. Plots samples chosen from this specification.

rsa

Processes the Source Angle specification. Plots samples chosen from this specification.

rst

Processes the Source Time specification. Plots samples chosen from this specification.

----Routines that process a User-Defined Source Routine----

getusrsorpart


Initializes the User-Defined Source routine.

----Routines that read/write a Source specification from/to a COG .sor file----

GetSorHeadOffset

Skips over the header record and positions the file for reading/writing source data.

3. Det Module Input Phase Routines



<u>detectin</u>

Processes the parsed DETECTOR Data Block that specifies the detectors in the problem.

DetDef

Processes the input parameters for most detector types (Boundary-Crossing, Reaction, Point)

DefVolPtDet

Processes the parameters for the Volume Point Detector type.

TRProc

Handles coordinate transformations needed for the Volume Point Detector.

<u>pulsein</u>

Processes the parameters for the Pulse Detector type.

DetMask

Sets up scoring masks that limit (in energy, time, angle,..) what the detector "sees".

MaskRegIn

Sets up masks that limit the Regions that the detector "sees".

DetRF

Processes the detector response functions.

DetBIN

Processes differential scoring bin structures.

GetUsrLib

For a user-supplied detector library, loads and verifies presence of user routines.

dyloadlib

Loads user library at runtime.


<u>dylinksub</u>

Dynamically links COG to the user-written routines.

DetList

Processes the List option.

4. RW Module Input Phase Routines




walkin

Processes the parsed WALK_XXX Data Blocks that specify parameters that modify the standard random walk methods.

walkin2

Identifies and stores the random walk modification parameters.

5. TXS Module Input Phase Routines



CheckXS

Checks validity of particle type, then reads the material dictionary and prints mixture definitions.

Crossin

Manages the reading of COG cross section files for a specified particle type.

RdLEX

Reads COG dictionary and translates names of the materials and isotopes specified in the MIX Block into ZA names used in the data libraries. Calls various checking routines (ChckGXS, ChckNXS, ChckPNUC, ChckSAB, and/or ChckXXS) to insure that the requested data (photon, neutron, photonuclear, thermal, and/or activation) are available in the specified COG data libraries.

MixDef

Prints mixture definitions in terms of their component isotopes ZA names.

RdDFG

Reads delayed-fission gamma data from the selected COG delayed gamma data library if BASIC Block 'neutron', 'photon', and 'delayedgamma' options are specified.

RdNXS

Reads neutron cross section data from the specified COG neutron data library if BASIC Block 'neutron' option is specified.

NTXSM

Forms total neutron cross section for each material in job if BASIC Block 'neutron' option is specified.

RdXXS

Reads neutron activation data from the selected COG activation data library if BASIC Block 'neutron' and 'activation' options are specified.

ATXSM

Forms total neutron activation cross section for each material in job if BASIC Block 'neutron' and 'activation' options are specified.

RdGXS

Reads photon data from the selected COG photon data library if BASIC Block 'photon' option is specified.

GTXSM

Forms total photon cross section for each material in job if BASIC Block 'photon' option is specified.

RdPNUC

Reads photonuclear data from the selected COG photonuclear data library if BASIC Block 'neutron', 'photon', and 'photonuclear' options are specified.

PNTXSM

Forms total photonuclear cross section for each material in job if BASIC Block 'neutron', 'photon', and 'photonuclear' options are specified.

PltXS

Plots total neutron and/or photon cross section for each material in job if I/O Block 'plotmxs' and BASIC Block 'neutron' and/or 'photon' options are specified.

PrntXS

Prints total neutron and/or photon cross section for each material in job if I/O Block 'printmxs' and BASIC Block 'neutron' and/or 'photon' options are specified.

PltNXS

Plots total neutron cross section for each isotope in job if I/O Block 'plotxs' and BASIC Block 'neutron' options are specified.

PltGXS

Plots total photon cross section for each element in job if I/O Block 'plotxs' and BASIC Block 'photon' options are specified.


PrntNXS

Prints total neutron cross section for each isotope in job if I/O Block 'printxs' and BASIC Block 'neutron' options are specified.

PrntGXS

Prints total photon cross section for each element in job if I/O Block 'printxs' and BASIC Block 'photon' options are specified.

6. EGS Module Input Phase Routines



EGSin

Processes the parsed EGS Data Block that specifies parameters for electron trtansport.

CheckPEGS

Checks that the PEGS data file has materials that match the COG materials list.


EGSInit

Initializes the EGS module and reads in the PEGS data file.

HATCH

EGS routine creates physics tables for electron/gamma-ray transport.

7. Pro Module Input Phase Routines



RdProSP

Reads proton data if BASIC Block 'proton' option is specified. Generates a table of proton stopping powers to be used in proton transport.

ProTXSM

Forms total proton cross section for each material in job if BASIC Block 'proton' option is specified.

ehlossr

Computes the relativistically-correct stopping power for heavy charged particles traversing a one-isotope medium.

BetheB

Computes the Bethe-Bloch Stopping Power Formula, without the Ce/Z term, for an isotope or mixture/compound.

SternInt

Computes the Sternheimer relativistic density effect correction to the heavy ion stopping power, for non-tabular compounds, and for elements and compounds at non-standard densities.

Stern2

Computes the Sternheimer relativistic density-effect correction to the heavy ion stopping power, for an element or a mixed material.

Stern3


Computes the Sternheimer relativistic density-effect correction to the heavy ion stopping power, for an array of particle energies. This version adjusts the tabular coefficients for changes in density.

3.5.2. Transport Phase Modules

Routines from the following Modules are used in the Transport Phase,

- RW
- Geom
- Det
- Sor
- TXS

1. RW Module Transport Phase Routines



Crwalk

Manages the criticality calculation. Runs batches to problem completion.

Srwalk

Manages the shielding transport calculation.

DetBound

Processes EHS and scores particles for the problem's Boundary-Crossing detectors. EHS is the Event History Store, a data array that accumulates all the events occurring during the tracking of a single source particle, and all of its secondary particles, for subsequent analysis.

DetReact

Processes EHS and scores particles for the problem's Reaction detectors.

DetPoint

Processes EHS and scores particles for the problem's Point detectors.

DetTrack

Processes EHS and scores particles for the problem's Tracklength Estimation detectors.

DetPulse

Processes EHS and scores particles for the problem's Pulse detectors.

DetUser

Proesses EHS and scores particles for the problem's User-Defined detectors.

InitRW

Initializes Random-Walk parameters

DoRestartCrit

Restarts a criticality job from a Restart Dump.

GetAvek

Computes criticality factor k at end of each batch.

DoRSD

Makes a Restart Dump during a criticality run

GetCritSrc

Produces the criticality source for the next batch.

OptPath

Computes optical path by region.

analysis

Stores particle data for subsequent analysis plots

GetNMult

Calculates neutron multiplication.

DoSummCP

Creates charged particle summary records in the EHS, for subsequent detector scoring.


retrace

Prints an event history summary for a specified particle.

wsor

Selects particles from a collision-based source.

----Additional RW Module Routines called from other Modules----



geomrw

Manages particle transport through main-level geometry.

geomrw1

As above, but for lower-level geometry units.

aget

Returns particle cutoff age (if any).

BStep

Steps particle across a geometry bounding surface.

CheckIntc

Checks validity of sector-exit surface intercept calculation.

GetNextSecList

Produces ordered sector list to help locate next sector entered by particle.

<u>rsb</u>

Performs Russian Roulette or splitting at a geometry boundary.

rsc

Performs Russian Roulette or splitting at a collision site.

<u>rww</u>

Performs Russian Roulette or splitting at a collision site, using weight windows.

wkchrn

Performs the Walk-Channel calculation.


geompe

Performs virtual particle transport though the main-level geometry for Point detectors.

geompe1

As above, but for lower-level geometry units.

2. Geom Module Transport Phase Routines




f


Evaluates a surface equation at the location of the particle.

<u>interc</u>

Finds the intercept between a particle's trajectory and a boundary surface.

3. Det Module Transport Phase Routines





score

Reviews a particle history in the EHS and calculates its scoring contribution to the problem's detectors.

scores

Sums the single-partcle score into the total scoring arrays.

InDRF

Converts detector scores from flux units into desired detector output quantities.

InMask

Checks if scoring particles pass through detector masks.


dose, Dose59, Dose91, ReactXS, EProd

Detector response function routines that convert basic flux scores into doses (various standards), reaction rates, or electron production.

to usrdet

Calls user-defined detector routines to process EHS tables and do custom scoring.

4. Sor Module Transport Phase Routines



L calls RW:geomrw

sour

If criticality problem...

Gets source particles from fission bank.

Elseif correlated source...

Reads random number parameters from previously generated .sor file such that each current source particle is initialized exactly as in previous run.

Elseif retrace option...

Uses BASIC Block 'RN' option to set the desired initial random number seeds and the SOURCE Block 'RETRACE' option to set the desired random number sequence #'s so as to regenerate (and edit) specific source particles.

Else...

If 'WRITESOURCE' option writes .sor file.

Calls... GsorP

GsorP

Generates source particles based on current source parameters

If 'CensusSorFlag' set...

Get source particles from previously generated census file.

Elseif 'UsrSorFlag' set...

Get source particles from user supplied source routine.

Else...

Calls... selt, sele, selp, and sela

<u>selt</u>

Get source particle age from input source parameters.

<u>sele</u>

Get source particle energy from input source parameters.

<u>selp</u>

Get source particle position from input source parameters.


<u>sela</u>

Get source particle direction from input source parameters.

uncpe (calls RW:geompe)

Computes the uncollided (source) contribution to a point flux estimate detector.

5. TXS Module Transport Phase Routines



Scat

Sets random walk flags (survival, secondary production) and random walk parameters (scattered direction bias, isotope/element bias, reaction bias), then calls...

DoWtStat

Determines min, max, and average weight by region and particle type.

<u>ScatN</u>

Neutron scattering routine.

ScatG

Photon scattering routine.

Niso (or NisoB, if isotope biasing set)

Determines in which isotope the scattering event occurs.

NElastic

Determines elastic reaction.

NNonEl

Determines non-elastic reactions.

Ncoll

Based on isotope and reaction, determines particle parameters (energy, position, direction, weight, age,...) of the scattered particle and stores the particle parameters for all secondary particles on the secondary bank.

Nreac (or **NReacB**, if reaction biasing set)

Determines reaction.

<u>GetNXG</u>

Stores particle parameters for (n,Xg) photons on secondary bank.

DoAGP

Stores particle parameters for activation photons on secondary bank.

Giso (or **GisoB**, if isotope biasing set)

Determines in which element the scattering event occurs.

GSurvival

Determines elastic and non-elastic reactions.

Gcoll

Based on element and reaction, determines particle parameters (energy, position, direction, weight, age,...) of the scattered particle and stores the particle parameters for all secondary particles on the secondary bank.

Greac (or **GreacB**, if reaction biasing set)

Determines reaction.

PhNuc

Stores particle parameters for photo-neutrons on secondary bank.

<u>DoPFE</u> (calls RW:geompe)


Driver for the computation of the collided contribution to a point flux estimate detector.

3.5.3. Output Phase Modules

Routines from the following Modules are used in the Output Phase,

- Geom
- Det
- RW
- TXS

1. Geom Module Output Phase Routines



geomin (see Geom Module Input Phase Routines)

COGCSP

Makes cross-section (2D) views of the geometry.

COGPP

Makes perspective views (3D) of the geometry.

CSPKey

Plots page of keys identifying patterns seen in cross-section plots.

DoPicP

Driver for making perspective views.

DoPix

Driver for making cross-section views.

fmed

For perspective views, finds the sector number of the first visible surface hit by the ray extending from the image-plane pixel at (px,py) through the pinhole and into the user's geometry.

FndInt

Finds intercepts of a sweep line with all visible surfaces of given unit.

FndSec

Finds sector(s) containing specified point P(x,y,z).

FnShEx

Finds the nearest exit surface from the unit shell sector.

pathl1

Driver for sweeping a line though the geometry and computing distances to sector boundaries. Used in sweeps, views, and volume calculations.

pathBC

Moves end of sweep line up to and across a boundary surface.

pathFI

Finds all intercepts of a sweep line with surfaces in specified unit.

pathFS

Finds sector containing a specified point P(x,y,z).

pathOu

Computes the output values for a pathl1 sweep.

pathRU

Terminates sweep through a lower-level unit and returns to higher level.

pathUn

Finds and processes intercepts in lower-level unit.

PlotLD

For perspective views, plots the edges found in the last sweep.

PrSwn

Prints results of a user-specified sweep.


SetVS

For perspective views, sets visibility of surfaces.

<u>volume</u>

Calculates volume (or mass) of specified sectors and prints results.

2. Det Module Output Phase Routines



actout

Prints calculated values in activation problems.

<u>plot3d</u>

Plots 2D bin results.

pro1d

Prints and plots detector results and statistics for 1D bins: time, energy, angle.

pro2d

Prints detector results and statistics for 2D bins: energy and time, time and angle, energy and angle.


pro24x

Prints detector results and statistics for all other 2D bins.

prout

Calculates, prints, and plots detector results. Writes .det file.

3. RW Module Output Phase Routines



<u>Srwalk</u> (see *RW Module Transport Phase Routine*)

<u>Crwalk</u> (see *RW Module Transport Phase Routine*)

analout

Prints detector results and statistics for all other 2D bins.

analout1

Makes analysis pictures showing collision sites.

analysis (see *RW Module Transport Phase Routine*)

critout

Prints and plots summary of batch k's for criticality jobs.

crit1out


Prints and plots fraction of fission neutrons with energies < E.

retrace (see RW Module Transport Phase Routine)

wtest

Performs the statistical w-test for convergence on criticality batches.

4. TXS Module Output Phase Routines



Crossin (see TXS Module Input Phase Routines)

<u>PltXS</u> (see TXS Module Input Phase Routines)

PrntXS (see TXS Module Input Phase Routines)

<u>PltNXS</u> (see TXS Module Input Phase Routines)

<u>PltGXS</u> (see *TXS Module Input Phase Routines*)

PrntNXS (see TXS Module Input Phase Routines)

PrntGXS (see TXS Module Input Phase Routines)

EditNXS

Prints a list of reactions for each isotope in job if DBUG Block 'xseditflag' is set.

3.5.4. Utility Routines

These are routines that have a single simple purpose and are called by various COG modules

1. Mem module routines

These are wrappers for the standard Unix memory-management routines and provide more detailed error messages if memory errors occur.

mallocc

Allocates a block of memory

mchlth

Resizes an allocated array.

<u>mmfail</u>

Issues error messages when allocation or resizing fails.

2. TXS module routines

RdAbs

Reads a file in absolute-address (unformatted) mode.

WrAbs

Writes a file in absolute-address (unformatted) mode.

3. RW module routines

RNG

Wrapper for the COG RNLF Rnadom Number Generator.

Called by: ~ 20 RW routines, 9 Sor routines, many EGS routines, 2 Det, 1 Geom, 4 Pro, numerous TXS routines.

3.5.5. Externally-Provided Software

These software libraries are provided by non-LLNL institutions and are not described further in this document

PGPlot Graphics Subroutine Library

This library supplies routines that support COG graphics output.

EGS4 Subroutine Library

This library supplies routines that support COG electron transport.

3.6. Data Structures

3.6.1. Geometry Data Structures

1. Surface Data Storage

The following **Table 1** lists the COG surface types, the relative CPU time required to solve the associated surface equation, and a brief equation description.

The expandable **csurf** array holds defining information for all the geometrical surfaces in the problem. **Table II** describes how the surface equations are stored in the **csurf** array for the various surface types of **Table I**.

Table 1 Internal Surface Types

TABLE 1 Internal Surface Types

Number	<u>Type</u>	<u>Time</u>	Description Description
1	Analytic	1	Plane parallel to yz plane: $x - x_0 = 0$
2	Analytic	1	Plane parallel to xz plane: $y - Y_0 = 0$
3	Analytic	1	Plane parallel to xy plane: $z - z_0 = 0$
4	Analytic	2	General plane: $c_0 + c_1x + c_2y + c_3z = 0$
5	Analytic	3	Sphere, center at origin: $x^2 + y^2 + z^2 - R^2 = 0$
6	Analytic	3	Sphere, center at (x_0, y_0, z_0) : $(x-x_0)^2 + (y-y_0)^2 + (z-z_0)^2 - R^2 = 0$
7	Analytic	3	Cylinder, axis parallel to z-axis: $(x-x_0)^2 + (y-y_0)^2 - R^2 = 0$
8	Analytic	3	Cylinder, axis parallel to y-axis: $(x-x_0)^2 + (z-z_0)^2 - R^2 = 0$
9	Analytic	3	Cylinder, axis parallel to x-axis: $(y-y_0)^2 + (z-z_0)^2 - R^2 = 0$
10	Analytic	3	Cone, axis parallel to z-axis $(x-x_0)^2 + (y-y_0)^2 - (A + Bz)^2 = 0$
11	Analytic	3	Cone, axis parallel to y-axis: $(x-x_0)^2 + (z-z_0)^2 - (A + By)^2 = 0$
12	Analytic	3	Cone, axis parallel to x-axis: $(y-y_0)^2 + (z-z_0)^2 - (A + Bx)^2 = 0$
13	Analytic	4	General second-degree surface: $C_0 + c_1x + c_2y + C_3z + c_4x^2 + c_5xy + c_6xz + c_7yz + c_8y^2 + c_9z^2 = 0$

TABLE 1 (continued)

Internal Surface Types

Number	Type	Time	Description
14	Analytic	6	General third degree surface: Number 13 expanded to include: $c_{10}x^3 + c_{11}x^2y + c_{12}x^2z + c_{13}xy^2 + c_{14}xyz + c_{15}xz^2 + c_{16}y^3 + c_{17}y^2z + c_{18}yz^2 + c_{19}z^3$
15	Analytic	10	Elliptical torus with axis coincident with z-axis: $(x^2 + y^2 + \gamma z^2 - 2\gamma z_0 z + B_0)^2 - A_0(x^2 + y^2)$
16	Analytic	10	Elliptical torus with axis coincident with y-axis: $(x^2 + z^2 + \gamma y^2 - 2\gamma y_0 y + B_0)^2 - A_0(x^2 + z^2)$
17	Analytic	10	Elliptical torus with axis coincident with x-axis: $(y^2 + z^2 + \gamma x^2 - 2\gamma x_0 x + B_0)^2 - A_0(y^2 + z^2)$
18	Analytic	20	General fourth degree surface: Number 14 expanded to include: $c_{20}x^4 + c_{21}x^3y + c_{22}x^3z + c_{23}x^2y^2 + c_{24}x^2yz + c_{25}x^2z^2 + c_{26}xy^3 + c_{27}xy^2z + c_{28}xyz^2 + c_{29}xz^3 + c_{30}y^4 + c_{31}y^3z + c_{32}y^2z^2 + c_{33}yz^3 + c_{34}z^4$
19	Psuedo	15	Non-reentrant figure founded by N plane surfaces with N greater than four. Each plane defined with the general equation (#4). A point must be on the negative side of all M surfaces to be within this figure.
20	Psuedo	6	Second degree surface bounded by two planes. To be within the figure, a point must be on the negative side of all three surfaces.
21	Psuedo	10	Inside one second degree figure and outside another second degree figure and between two planes. A point is within the figure if it is on the negative side of both planes and on the negative side of the outer second degree surface and on the positive side of the inner such surface. Not referenced by code inputs except with the "DIRECT" statement.

TABLE 1 (continued) Internal Surface Types

Number	Type	<u>Time</u>	Description
22	Psuedo	30	A surface formed by a series of second degree surfaces, each of which is to be used only between two bounding planes. At any bounding plane, the intersection of the two second degree surfaces used on either side of the plane describes the same identical curve. The defining surfaces reach a single point at each of the two ends of the figure. The surface is defined as being positive at points outside the closed figure and negative inside. The first plane is used only on its positive side while the last plane is used only on its negative at points within the figure.
23	Psuedo	30	A surface formed by putting together a series of four-sided prisms. The set has a common top and bottom plane and adjacent prisms have common sides that are exactly coincident with each other. To be within the figure, the top and bottom planes must be negative as well as the two side planes. The bounding planes must be positive for the first boundary and negative for the second.
24	Psuedo	30	Like #22 except that the ends do not necessarily reach a single point and the intersections of adjacent second degree curves with their bounding plane do not necessarily result in the same curve.
25	Psuedo	30	Surface is defined by a tabular representation with a fixed x and a fixed y grid and corresponding values of z provided at the x,y intersections. The values of z between the tabular values are obtained by linear interpolations in both x and y (a second degree fit).
26	Psuedo	20	Surface defining the outside of a Yin-Yang coil configuration.
27	Psuedo	8	Similar to #21 but without the restraint of being between two plane surfaces. Again, not referenced by normal code inputs except with the "DIRECT" input.
28	Psuedo	20	Inside one non-reentrant figure bounded by N plane surfaces while being outside of another non-reentrant figure also bounded by another set of M plane surfaces. Not referenced by code inputs except with the "DIRECT" option.

Table 2 Surface Definition Data Storage

Table II Surface Definition Data Storage

Surface Definition Data Storage			
Number	Relative Location	Data Stored	Comment
1	L	x ₀	Plane yz
2	L	y ₀	Plane xz
3	L	z_0	Plane xy
4	LL+3	c ₀ , c ₁ , c ₂ , c ₃	General Plane
5	L	R^2	Sphere @ origin
6	LL+3	x_0, y_0, z_0, R^2	General sphere
7	LL+2	x_0, y_0, R^2	Cylinder-Z
8	LL+2	x_0, z_0, R^2	Cylinder-Y
9	LL+2	y_0, z_0, R^2	Cylinder-X
10	LL+5	x_0, y_0, A, B, AB, B^2	Cone-Z
11	LL+5	x_0 , z_0 , A, B, AB, B ²	Cone-Y
12	LL+5	y_0 , z_0 , A, B, AB, B ²	Cone-X
13	LL+9	c ₀ , c ₁ , c ₉	General 2 nd degree
14	LL+19	c ₀ , c ₁ , c ₁₉	General 3 rd degree
15	L	$A_0 (= 4z_0^2)$	Elliptical Torus - Z
	L+1	$B_0 (= x_0^2 - a^2 + z_0^2)$	a = minor radius in plane of torus
	L+2	$\gamma (= b^2/a^2)$	b = minor radius in plane perpendicular to torus
	L+3	$C_0 (= 2 \gamma z_0)$	
16	L	$A_0 (= 4x_0^2)$	Elliptical Torus -Y
	L+1	$B_0 (= x_0^2 - a^2 + y_0^2)$	
	L+2	$\gamma (= b^2/a^2)$	
	L+3	$C_0 (= 2 \gamma y_0)$	

Table II (continued) Surface Definition Data Storage

Number	Relative Location	Data Stored	Comment
17	L	$A_0 (= 4y_0^2)$	Elliptical Torus - X
	L+1	$B_0 (= y_0^2 - a^2 + x_0^2)$	a = minor radius in plane of torus
	L+2	$\gamma (= b^2/a^2)$	b = minor radius in plane perpendicular to torus
	L+3	$C_0 (= 2 \gamma x_0)$	
18	LL+34	c ₀ , c ₁ , c ₃₄	General 4 th degree equation
19	L	N: number of bounding surfaces	General box
	L+1L+N	Temp. storage for $f_n(x,y,z)$	
	L+N+1 L+N+4	c ₀ , c ₁ , c ₂ , c ₃ for 1st surface	
	L+N+5 L+N+8	As above, for 2 nd surface	
		etc.	
20	L	Temp. storage for $f_n(x,y,z)$, top plane	Finite cylinder
	L+1	As above, for bottom plane	
	L+2	As above, for 2 nd degree surface	
	L+3L+6	c_0 , c_1 , c_2 , c_3 for top plane	
	L+7L+10	As above, for bottom plane	
	L+11L+20	c ₀ , c ₁ ,c ₉ for 2 nd degree surface	

Table II (continued) Surface Definition Data Storage

Number	Relative Location	Data Stored	Comment
21	L	Temp. storage for f(x,y,z) for top plane	Volume between one 2 nd degree surface and another, bounded by two planes
	L+1	As above, for bottom plane	
	L+2	As above, for outer 2 nd degree surface	
	L+3	As above, for inner 2 nd degree surface	
	L+4L+7	c_0 , c_1 , c_2 , c_3 for top plane	
	L+8L+11	As above, for bottom plane	
	L+12L+21	c ₀ , c ₁ , c ₉ for outer 2 nd degree surface	
	L+22L+31	As above, for inner 2 nd degree surface	
22	L	N: number of 2nd degree surfaces	Surface of revolution
	L+1L+4	c ₀ , c ₁ , c ₂ , c ₃ coefficients for 1st plane	The defined figure does not exist on the negative side of this plane.
	L+5L+8	As above, for 2 nd plane	
	L+1+4N L+4+4N	As above, for N+1st plane	The defined figure does not exist on the positive side of this plane.
	L+5+4N L+14+4N	c ₀ , c ₁ , c ₉ for first 2 nd degree surface	Used between 1st and 2nd planes.
	L+15+4N	Coef. of remaining 2 nd degree surfaces	

Table II (continued) Surface Definition Data Storage

Number	Relative Location	Data Stored	Comment
23	L	N: the number of prisms	Volume between one 2 nd degree surface and another, bounded by two planes
	L+lL+4	c_0 , c_1 , c_2 , c_3 coefficients for the top-most plane	
	L+5L+8	As above, for the bottom- most plane	
	L+9L+12	As above, for the first defined plane	The defined figure does not exist on the negative side of this plane.
	L+13L+16	As above, for the 2nd defined plane	This is between the first and second prism.
	L+17L+20	As above, for the 3rd defined plane	
	L+9+4N	As above, for the (N+1)st defined plane	The figure is undefined on the positive side of this plane.
	L+13+4N	As above, for outer plane of the first prism.	Must be negative to be on the inside of the prism.
	L+17+4N	As above, for inner plane of the first prism	Must be negative to be on the inside of the prism.
	L+21+4N	As above, for outer plane of the 2nd prism.	
		Etc.	
24			Identical to surface 22

Table II (continued) Surface Definition Data Storage

Number	Relative Location	Data Stored	Comment
25	L	N: the number of intervals in the x-direction	Surface is defined by a tabular grid for $z(x,y)$.
	L+l	M: the number of intervals in the y-direction	
	L+2L+2+N	x-grid values (increasing order)	
	L+3+N L+3+N+M	y-grid values (increasing order)	
	L+4+N+M	z-values on the x,y grid.	$z(x_i, y_j)$ is stored at: L3+i+(j-1)(N+1), where L3 =L+3+N+M.
26	LL+5	Temporary storage for 6 cylinders' coefs	Yin_Yang Coil
	L+6L+22	Temporary storage for 17 planes' coefs	
	L+23L+32	c0, c1,c9 for cylinder 1	
	L+33L+42	As above, for cylinder 2	
	L+73L+82	As above, for cylinder 6	
	L+83L+86	c0, c1,c2, c3 for plane 1	
	L+147L+150	c0, c1, c2, c3 for plane 17	

Table II (continued)
Surface Definition Data Storage

Number	Relative Location	Data Stored	Comment
27	L	Temporary storage for f(x,y,z) defining outer surface	
	L+l	Temporary storage for f(x,y,z) defining inner surface	
	L+2L+11	c0, c1,c2c9 for outer surface	
	L+12L+22	c0, c1,c2c9 for inner surface	
28	L	N: number of surfaces	
	L+1L+2N	Temporary storage for	Outer surfaces followed
		$f_{n}(x,y,z)$	by inner surfaces.
	L+2N+1L+2N+4	c0, c1, c2, c3 for first outer surface	
	L+2N+5L+2N+8	c0, c1, c2, c3 for second outer surface	
	•••••		
	L+6N+1L+6N+4	c0, c1, c2, c3 for first inner surface	
	L+6N+5L+6N+8	c0, c1, c2, c3 for second inner surface	

2. Volume Data Storage

The basic COG volume element is the sector, which is a volume bounded by surfaces whose descriptions are stored in the **csurf** array outlined above.

Each sector is defined by a Sector Description record stored in the **sd** array. An **sd** record has a variable length depending only on the number of surfaces used to describe the sector's boundaries.

Table 3 Sector Description (sd) Array

Location	Item	Description	Type
1	nsty	Type of sector	Integer
2	nmat	Material number (if nsty=1)	Integer
	nuntn	Unit number (if $nsty = 2$)	
3	nreg	Region number	Integer
4	xdf	Density factor	Real
5	neqs	Count of surfaces bounding	Integer
		sector	
6	nsecnCog	COG-assigned sector number	Integer
7 - 8	names	Sector name	String
9	nsecnUser	User-specified sector number	Integer
10	dens	Material density	Real
11 - 36	trans (array)	Coordinate transformation	Real
		Matrix	
37 –	nsureq (array)	Internal surface number, with	Integer
36+neqs		sign, for each bounding surface	
37+neqs –	nsureqi (array)	Index into array of user surface	Integer
36+2*neqs		numbers, for each bounding	_
		surface	
37+2*neqs	kpos (array)	Index into ordering array which	Integer
_		determines order of surface	_
36+3*neqs		evaluation	

3.6.2. Event History Storage (EHS) Data Structures

The **EHS** array contains the event history of each primary (source) particle and those of its secondaries (particles arising from collisions in the problem materials). COG computes detector scores at the end of each source particle trajectory, when it and all its "daughter" particles have been tracked until they escaped the system or were absorbed. Each event in the history of a source particle and its progeny - such as a boundary crossing, a scattering, or an absorption event - is recorded in the Event History Store (EHS) array.

Each event is stored as a fixed-length record in the EHS array.

Table 4 Event History Store Record

Record Item name	Description
nevent	event type
x,y,z	position of event site
u,v,w	particle direction at event
	site
age	particle age
eng	particle energy
ntype	particle type number
vel	particle velocity
wate	particle statistical weight
noc	number of collisions
imat	material number
ireg	region number
tdf	density factor
stot	total cross section
nreact	reaction number
xmfp	mean-free-paths left to
	travel
edep	energy deposition times
	statistical weight
nsave	number of sector
	containing particle
xlambda(1)-(2)	decay constants for
	activation
ex1	distance to next boundary
cosn	cosine of angle between
	trajectory and surface
	normal, for case
	nevent=40

Table 5 Events

Event # (nevent)	Description
10	particle taken from source
20	particle taken from secondary bank
30	particle taken from fission bank
40	crossed a boundary between two different regions
50	enters into a collision
51	exits from a collision
52	modified by path stretching
60	encounters a reflecting boundary
61	returns from a reflecting boundary
70	encounters an albedo boundary
71	returns from an albedo boundary
80	encounters a periodic boundary
81	returns from a periodic boundary
90	particle absorbed in an infinite absorber
91	terminated because energy out of range of cross sections
100	encounter a vacuum boundary (or its equivalent)
120	entered into a russian roulette game
121	killed by losing a russian roulette game
122	survived a russian roulette game
130	terminated by a time cut-off imposed by the geometry description
131	terminated by time constraint
135	encounters a time boundary imposed by the geometry's description
140	enters into a weight window modification
141	exits from a weight window modification
150	entered into a splitting modification
151	exited from a splitting modification
162	terminated in forced collision process
180	terminated due to a problem specification error

3.6.3. Input File

See user guide

3.6.4. Common Block Usage

See include files

INDEX

	dose	21
A	Dose59	21
actout	Dose91	21
aget	DoSummCP	18
analout	DoWtStat	24
analout1	dylinksub	
analysis	dyloadlib	
asmrd	Ž	1 1
ATXSM 13	\boldsymbol{E}	
7.17.XXXIVI	EditNXS	29
В	EGS (Electron Gamma-Ray Shower Modul	
BetheB	EGS4 Subroutine Library	_
	EGS4 Subroutine Library	
BStep		
\boldsymbol{c}	EGSInit	
	ehlossr	
ChckGXS	EProd	21
ChckNXS	F	
ChckPNUC 12	_	
ChckSAB	f 20	
ChckXXS	ffinp	
CheckIntc	fmed	26
CheckPEGS14	FndInt	26
CheckXS	FndSec	26
COGCSP	FnShEx	26
COGPP26		
crit1out	\boldsymbol{G}	
critin	Gcoll	24
critout	Geom (Geometry Module)	
Crossin	geomin	
Crwalk	geompe	
CSPKey	geompe1	
C51 Key	geomrw	10
D	geomity.1	10
D 07 ID/D /	geomrw1	
DefVolPtDet	GetAvek	
Det (Detector Module)	GetCritSrc	
DetBIN11	GetNextSecList	
DetBound	GetNMult	
DetDef10	GetNXG	
detectin	GetSorHeadOffset	
DetList11	GetUsrLib	
DetMask 11	getusrsorpart	9
DetPoint	Giso	24
DetPulse	GisoB	24
DetReact 17	Greac	24
DetRF11	Corre	24
	GreacB	
DetTrack18		5
DetTrack 18 DetUser 18	Grf (Graphics Module)	
DetUser	Grf (Graphics Module)GsorP	22
DetUser 18 DoAGP 24	Grf (Graphics Module) GsorP GSurvival	22
DetUser 18 DoAGP 24 DoPFE 25	Grf (Graphics Module)GsorP	22
DetUser 18 DoAGP 24 DoPFE 25 DoPicP 26	Grf (Graphics Module) GsorP GSurvival	22
DetUser 18 DoAGP 24 DoPFE 25 DoPicP 26 DoPix 26	Grf (Graphics Module) GsorP GSurvival GTXSM	22 24 13
DetUser 18 DoAGP 24 DoPFE 25 DoPicP 26	Grf (Graphics Module) GsorP GSurvival GTXSM	22 24 13

I	Pro (Proton Transport Module)	5
ingluda (Ingluda Madula) 5	pro1d	27
include (Include Module)	pro24x	28
InDRF 21	pro2d	28
InitRW	ProTXSM	15
InMask	prout	
interc	PrSwp	
L	pulsein	
LF (Lagged Fibonacci Random Number	R	
Generator Module) 5	RdAbs	30
M	RdDFG	
171	RdGXS	
Mag (Magnetic Field Module)5	RdLEX	
Main (Main Module)3	RdNXS	
mallocc		
MaskRegIn11	RdPNUC	
mchlth30	RdProSP	
Mem (Memory Management Module) 5	RdXXS	
MixDef	ReactXS	
mmfail 30	retrace	,
MPI (Message Passing Interface Module) 6	RNG	30
MPI (Message Passing Interface Module) 6	rsa9	
N	rsb	19
"	rsc19	
Ncoll 24	rse9	
NElastic	rsp	9
Niso	rst 9	
NisoB24	RW (Random Walk Module)	1
NNonEl	rww	
Nreac	1ww	20
NReacB24	\boldsymbol{S}	
NTXSM		22
	Scat	
0	ScatG	
OptPath	ScatN	
Optr atti 18	score	21
P	scores	21
100	sela	23
pathBC	sele	23
pathFI26	selp	23
pathFS	selt	
path1126	SetVS	
pathOu26	Sor (Source Module)	
pathRU	sorin	
pathUn27	sour	
PGPlot Graphics Subroutine Library 30	Srwalk	
PhNuc 25		
plot3d27	Stern2	
PlotLD	Stern3	
PltGXS	SternInt	
PltNXS	surfac	8
PltXS	T	
	•	
PNTXSM	to_usrdet	21
PP (Parallel Processing Support Module)	TRProc	11
PrntGXS	TXS (Total Cross Section Module)	4
PrntNXS		
PrntXS		

U	W
uncpe	
volume	WrAbs